

Dane techniczne dla produktu: BK090202--

Obudowa natynkowa 1x18 mod. IP65, 1000V DC

odporna na UV, materiał ABS, drzwi transparentne



SCHRACK-Info

- Wall-mounted enclosures with one transparent door inclusive UV-Protection
- Lock: Pressure-operated mechanism, a small cylinder can be installed
- Cable Entry by elastic rubber membranes
- Includes PE and N terminals
- Halogen-free plastic materials
- Protection class II
- UV stability and weather resistant
- Rated voltage 400VAC, 1000VDC

- Ambient temperature: -25° to +85°C
- Material: ABS
- Degree of protection IP65
- Resistance to impact: IK07
- RAL7035 light grey

Dane techniczne

Szerokość (mm)	432,00
Wysokość (mm)	288,00
Głębokość (mm)	160,00
Waga (kg)	2,54
EAN	9004840817935
Straty mocy (W)	-35,00
Min. temperatura otoczenia (°C)	-25
Maks. temperatura otoczenia (°C)	85

Lista produktów

OPIS	Nr katalogowy
Obudowa natynkowa 1x18 mod. IP65, 1000V DC odporna na UV, materiał ABS, drzwi transparentne	BK090202
Dodatkowe akcesoria	
Wkładka półcylindryczna / zamek do obudów BK09 IP65	BK090097