

Dane techniczne dla produktu: DS428010-B

Szafa stojąca 19" 42U 800/ 1000/ 1970mm, drzwi przeszklone

RAL9005 Czarny



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 42U
- Width: 800mm
- Depth: 1000mm
- Colour:
 - Black RAL9005.
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.
- External hinge system allows up to 180 degree door opening angle.
- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).

- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U
 - D800 - Opening: 10U, Covering: 1 x 10U
 - D900 - Opening: 12U, Covering: 1 x 12U

- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19"-Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Dane techniczne

Szerokość (mm)	800,00
Wysokość (mm)	1.970,00
Głębokość (mm)	1.000,00
Waga (kg)	104,20
Min. temperatura otoczenia (°C)	0
Maks. temperatura otoczenia (°C)	40
Odpowiednie dla jednostek U	42U-1970mm
Kolor	RAL 9005 (czarny)

Lista produktów

OPIS	Nr katalogowy
Szafa stojąca 19" 42U 800/1000/1970mm, drzwi przeszklone RAL9005 Czarny	DS428010-B
Dodatkowe akcesoria	
Cokół para boczna 1000mm, wysokość 120mm RAL9005 Czarny	DSOT1210-B
Cokół front/tył 800mm, wysokość 120mm RAL9005	DSOF1280-B
Półwkładka cylindryczna z kluczem EK 333 Pasuje do szaf DS, zestawu DTZLOCK02- (do drzwi szaf DT) oraz zamków HS w obudowach termoutwardzalnych PPOxxxxxxx. Zawiera śrubkę mocującą M5x16mm. Jeden klucz.	DV900333S

Lista produktów

OPIS	Nr katalogowy
Dodatkowe akcesoria	
Maskownica dachowa ze szczotką do szaf typu DSx, 2U, czarna RAL 9005	DBK24800-B
Panel 2-wentyl. dachowy z termost. do DSx, 19", 4U, RAL9005 Do obudów wolnostojących DS./DSZ oraz DSS	DLT44802-B
19" organizer kablowy, poziomy, 5 uchwytów metal. 80x40mm RAL9005 Czarny	DBC14805-B
19" organizer kablowy, poziomy, 5 uchwytów 75mm z tworzywa RAL9005 Czarny	DBK14805-B
19" Półka, obciążalność 80kg, Gł.450mm, 1U, RAL9005	DFS14845-T
19" listwa zasil. 9xSchuko, profil ALU 1U, 3m-kabel, RAL7035	IU070114-3
19" listwa zasilająca, 7x230V Schuko, z ochroną PP, 1.25U kabel długości 2m, RAL7035	IU070113
19" listwa zasilająca 9x230V Schuko, 1U, wyłącznik, czarna kabel 2m, czarna, ALU	Q7070114-A
19" listwa zasilająca 7x230V Schuko z ochroną PP kabel 2m, czarna, ALU	Q7070113-A
Listwa zasilająca 12xC13, 6xSchuko, wejście CEE 16A Listwa pasywna	HSMPP312
Uchwyt PDU do obudów DS i DSZ o szerokości 800 mm, 1U 1 para = 2 szt., zawiera materiał montażowy	DSPDU010
Komplet śrub montażowych 50xM6	DSSRA050
19" płyta montażowa, 14U, perforowana stalowa Zawiera śruby i nakrętki	DMP1914
Lampka LED rack, magnes, 230VAC z czujnikiem otwarcia drzwi działa automatycznie po otwarciu drzwi, zewnętrzne zasilanie	DTLIGHT01
19" Switch, 24xRJ45 10/100/1000, cichy, zasilacz wew 19" metalowa obudowa	QLGSW2457
19" panel kros. 24-porty (SFA)(SFB), niewyposażony, 1U, ECO kolor czarny, zestaw jedno-elementowy	HSER0240SP