

Dane techniczne dla produktu: DSZ428020-

Szafa szkieletowa 19" 42U 800/1200/1970mm, drzwi przeszkłone



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 42U
- Width: 800mm
- Depth: 1.200mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg
- Degree of protection: IP20

- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.
- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.

- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Dane techniczne

Szerokość (mm)	800,00
Wysokość (mm)	1.970,00
Głębokość (mm)	1.200,00
Waga (kg)	110,80
Min. temperatura otoczenia (°C)	0
Maks. temperatura otoczenia (°C)	40
Odpowiednie dla jednostek U	42U-1970mm
Kolor	RAL 7035 / RAL 5005 (jasnoszary / niebieski)

Lista produktów

OPIS	Nr katalogowy
Szafa szkieletowa 19" 42U 800/1200/1970mm, drzwi przeszklone	DSZ428020
Dodatkowe akcesoria	
Półwkładka cylindryczna z kluczem EK 333 Pasuje do szaf DS, zestawu DTZLOCK02- (do drzwi szaf DT) oraz zamków HS w obudowach termoutwardzalnych PPOxxxxxxx. Zawiera śrubkę mocującą M5x16mm. Jeden klucz.	DV900333S
Maskownica dachowa ze szczotką do szaf typu DSx, 2U, szara RAL 7035	DBK24800
Panel 2-wentyl. dachowy z termost. do DSx, 19", 4U, RAL7035 Do obudów wolnostojących DS./DSZ oraz DSS	DLT44802-A
Cokół para boczna 1200mm, wysokość 120mm	DSOT1220
Cokół front/tył 800mm, wysokość 120mm, z filtrem RAL7035	DSOF1283
19" organizer kablowy, poziomy, 5 uchwytów metal. 80x40mm	DBC14805
19" organizer kablowy, poziomy, 5 uchwytów 75mm z tworzywa	DBK14805
Półka 19" stała o gł. 450mm, obciążal. 80kg, 1U, perforowana	DFS14845-C
19" listwa zasil. 9xSchuko, profil ALU 1U, 3m-kabel, RAL7035	IU070114-3
19" listwa zasilająca, 7x230V Schuko, z ochroną PP, 1.25U kabel długości 2m, RAL7035	IU070113
19" listwa zasilająca 9x230V Schuko, 1U, włącznik, czarna kabel 2m, czarna, ALU	Q7070114-A

Lista produktów

OPIS	Nr katalogowy
Dodatkowe akcesoria	
19" listwa zasilająca 7x230V Schuko z ochroną PP kabel 2m, czarna, ALU	Q7070113-A
Komplet śrub montażowych 50xM6	DSSRA050
19" płyta montażowa, 14U, perforowana stalowa Zawiera śruby i nakrętki	DMP1914
Lampka LED rack, magnes, 230VAC z czujnikiem otwarcia drzwi działa automatycznie po otwarciu drzwi, zewnętrzne zasilanie	DTLIGHT01
19" Switch, 24xRJ45 10/100/1000, cichy, zasilacz wew 19" metalowa obudowa	QLGSW2457
19" panel krosowy 24-portowy, niewyposażony, 1U jasnoszary, zamek patchcordu - wpinany od dołu	HSER0240GS