



Dane techniczne dla produktu: HLP23TC00F

Patchcord Duplex ST/UPC - SC/UPC, 50/125µm OM3, LSOH

aqua, 0.5m



SCHRACK-Info

Multimode patch cords are mainly used for short-distance communication with high transmission rates, for example within a building or on a campus. The multimode patch cords are equipped with an LSOH-jacket. These comply with IEC or EIA-TIA standards. These multimode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- ST/UPC - SC/UPC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Multimode cabled fiber conforms to ITU-T G.651.1, IEC 60793-2-10
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks


- ATM, SONET and WDM

OM3 LS0H

Dane techniczne

Norma	IEC 61300-3-4 / IEC 61300-3-6
Połączenie zgodnie z normą	IEC 61754
kombinacja połączeń światłowodowych	C/ST
Długość kabla krosowego (mb)	0,50
Typ włókna	50/125µm OM3 wielomodowe
Płaszcz kabla	LS0H
Kolor	turkusowy
Typowa tłumienność wtrąceniowa (IL) (dB)	≤0,25
Typowa tłumienność odbiciowa (RL) (dB)	≥30
Min. temperatura otoczenia (°C)	-20
Maks. temperatura otoczenia (°C)	60
Szerokość (mm)	150,00
Wysokość (mm)	200,00
Waga (kg)	0,04

Rysunek wymiarowy: Patchcord Duplex ST/UPC - SC/UPC, 50/125µm OM3, LS0H



Patchcord Duplex ST/UPC - SC/UPC, 50/125µm OM3, LS0H
aqua, 0.5m

HLP23TC00F