

Dane techniczne dla produktu: HSATWT50S-

Wspornik maszt. SAT 50 cm, rury maszt. śred.= 38-60 mm, stal

Ocynkowany, dwuczęściowy



SCHRACK-Info

Hot-dip galvanized steel wall bracket, 2-part, for the securely attaching a mast tube with a diameter of Ø 38 to 60mm to the wall. Wall distance: 150mm, adjustable by 10cm. Mast tube not included.

TECHNICAL DATA

- Material: Quality steel
- Struts : Flat profile 30 x 5mm
- Surface: hot-dip galvanizing approx. 80
- Wall distance: 500mm, adjustable up to 10cm
- twist-proof: with 2x twist-proof claws
- consisting of: 1x bipod and 1x tripod holder
- suitable for mast tubes : Ø 38 to 60mm

Dane techniczne

Długość (mm)	520,00
Szerokość (mm)	560,00
Wysokość (mm)	50,00
Waga (kg)	3,90
Min. temperatura otoczenia (°C)	-40
Maks. temperatura otoczenia (°C)	60

Lista produktów

OPIS	Nr katalogowy
Wspornik maszt. SAT 50 cm, rury maszt. śred.= 38-60 mm, stal Ocynkowany, dwuczęściowy	HSATWT50S
Dodatkowe akcesoria	
SAT Maszt 2000mm, Ø50, Stal	HSATMM20S
SAT Maszt 2000mm, Ø60, Stal	HSATMM20S6
SAT Maszt 3000mm, Ø50, Stal	HSATMM30S
SAT Maszt 3000mm, Ø60, Stal	HSATMM30S6