




Dane techniczne dla produktu: HSELT249HP

FO Splicebox MA14 24LSH/PC (Compact), 9µm, OS2, 19", 1U

RAL7035, PREMIUM



SCHRACK-Info

DESCRIPTION

- Material: Steel sheet, powdered RAL7035
- Telescopic extension
- LSH (identical in construction to E2000®) Breakouts arranged in a row
- rear left oblique/straight outlet with 1x PG16 and blind plug for right/left mounting
rear right closed with blind cover
- Threaded bushing for strain relief (both sides, screwed)
- Anti-rotation device for splice cassette
- Labeling strip screwed
- 2pcs. cable guide bracket for front mounting enclosed, black
- Front panel numbered (1 - 12)
- Box lid screwed to the side
- Laser symbol printed on angle right, Schrack Technik logo printed on left

EQUIPMENT

- 12x LSH Compact couplers (identical in construction to E2000®) mounted with assembly clip (snap-in) for 1.5mm sheet thickness
- 24x LSH (identical in construction to E2000®) pigtails, inserted, plugged in and prepared for splicing
- 1x PG16 screw connection

- 4x Drillers glued (fiber guide rings)
- 2x splice cassette + cover
- 1x cable support with cable comb for pre-assembled cables included

SPLICE CASSETTE

- 2pcs. with 2 integrated 12-fold splice combs for shrink splice protection and cover
Brand Schrack Technik: 2x HSELSZSK01 + 2x HSELSZSK05 + 1x HSELSZSK03

COUPLER

- LSH Compact (identical in construction to E2000®)
 - Singlemode: Brand s4u
 - Order code: 910140

PIGTAILS

- LSH (identical in construction to E2000®)
 - Singlemode: Brand s4u UPC
 - Order code: LW008153
- Fiber:
 - Length: 2m
 - Singlemode: Brand Corning® SMF-28+ // ITU-T G.657.A1 and fully conform with ITU-T G.652.D

STANDARDS

- EN 50173-x
- IEC 61753-1
- IEC 61300-3-34


Dane techniczne

Szerokość (mm)	483,00
Wysokość (mm)	44,00
Głębokość (mm)	290,00
Waga (kg)	2,48
Kolor	RAL 7035 (jasnoszary)
Min. temperatura otoczenia (°C)	-10
Maks. temperatura otoczenia (°C)	70
Typ włókna	9/125µm OS2 jednomodowe / G.652.D / G.657.A1
Ilość włókien	24
adapter	LSH (konstrukcja typu E2000®)

Dane techniczne: FO Splicebox MA14 24LSH/PC (Compact), 9µm, OS2, 19", 1U

	Singlemode
	Typisch
	[dB]
Einfügedämpfung (IL)	< 0,12
Rückflussdämpfung (RL)	> 50

Rysunek wymiarowy: FO Splicebox MA14 24LSH/PC (Compact), 9μm, OS2, 19", 1U



Lista produktów

OPIS	Nr katalogowy
FO Splicebox MA14 24LSH/PC (Compact), 9μm, OS2, 19", 1U RAL7035, PREMIUM	HSELT249HP
Dodatkowe akcesoria	
Światłowód A/I-DQ(ZN)BH 24x9/125μm OS2, LS0H-3, Dca Niemetaliczna ochrona przed gryzoniami, czarny płaszcz 8 mm, uniwersalny, 3500N	HSIAIBH249
FO osłonka spawów fusion 60mm	HELSP00011
FO osłonka spawów fusion 40mm	HELSP00010