

Dane techniczne dla produktu: LID13663--

Pasek LED Marra 14,4W/m 60LED/m 3000K 1050lm/m 24VDC IP68

Ściemniany, rolka 5m



Informacja o produkcie

Waterproof flexible LED light strip, with SMD2835 LEDs, 70LEDs/meter, 14,4W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing, IP68. Can be cut every 10cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Dane techniczne

Barwa światła	Ciepła biała
Temperatura barwowa (K)	3000
Stopień oddawania barw (Ra)	≥90
Żywotność	30.000h
Możliwość ściemniania	w zależności od zasilacza tak
Klasa ochrony	III
Stopień szczelności	IP68
EEC	G
Klasa efektywności energetycznej	G
Rodzaj oprawy oświetleniowej	pasek LED
Źródło światła w zestawie	Tak

Dane techniczne - kontynuacja

Gniazdo	Płytki LED
Skuteczność świetlna (lm/W)	72
Sterownik	należy zamówić oddzielnie
Napięcie pracy DC (V)	24
Napięcie wejściowe DC (V)	24
Montaż	naścienny na podłożu sufitowy natynkowy
Materiał	Silikon
Długość (mm)	5000
Szerokość (mm)	10
Dodatkowe akcesoria	LID16631--
Strumień świetlny / m (lm/m)	1050

Lista produktów

OPIS	Nr katalogowy
Pasek LED Marra 14,4W/m 60LED/m 3000K 1050lm/m 24VDC IP68 Ściemniany, rolka 5m	LID13663
Dodatkowe akcesoria	
Uchwyt montażowy do LID16609	LID16631