

Dane techniczne dla produktu: NLCC24-20-

Low power system CoreCompact24 24V 4/20

4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W
1h / 85W 3 h / 25W 8 h, optionally: Battery extension (NLBALI020), h x w x d: 455 x 250
x 230 mm



Dane techniczne

Długość (mm)	230,00
Szerokość (mm)	250,00
Wysokość (mm)	455,00
Waga (kg)	13,00

Lista produktów

OPIS	Nr katalogowy
Low power system CoreCompact24 24V 4/20 4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W 1h / 85W 3h / 25W 8h, optionally: NLCC24-20 Battery extension (NLBALI020), h x w x d: 455 x 250 x 230 mm	
Dodatkowe akcesoria	
E30 fire protection panel for LPS MicroControl MI with fan Outside dimensions: 918 x 711 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 70kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMIE30
Plexiglas cover with lock for LPS Microcontrol	NLPLXMIC
3-phase line monitor with bus communication for Multicontrol	NLMCLM
PC230 3-fazowy monitor faz	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Panel kontrolny z wyświetlaczem LCD i poł. z magistralą Do oprav awaryjnych	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S