

Dane techniczne dla produktu: NLEXU011 SC

EX-protect.emerg.luminaire design EX zone2/22 LED 1h 230V AC

without pictogram, wall or ceiling surface mounting, IP66, type: MULTIBASET-N-LED-1300-4K, 320lm



Dane techniczne

Długość (mm)	338,00
Wysokość (mm)	176,00
Głębokość (mm)	110,00
Waga (kg)	1,08
Rodzaj oprawy oświetleniowej	awaryjna
EB-ZB	Oprawy autonomiczne
Funkcja	autotest
Wersja	oprawy do stref Ex
Design / Seria	EX
Kolor	szary
Czas podtrzymania (H)	1
Źródło światła	LED (8W)
Strumień świetlny	320

Dane techniczne - kontynuacja

Zakres napięcia (V)	230V AC 50Hz ±20%
Akumulatory (V/Ah)	3,6/1,6 NiCd
Stopień szczelności	IP66
Montaż	naścienny sufitowy natynkowy
Min. temperatura otoczenia (°C)	5
Maks. temperatura otoczenia (°C)	40
AA klasa E 8101	AA5

Abstandstabelle - Min. Beleuchtungsstärke auf der Mittellinie +/- 0,5m: 1lx - Wartungsfaktor 0,80, 1h Autonomiezeit

					
2,00	3,71	9,44	9,03	8,62	3,44
2,50	3,95	10,17	9,77	9,38	3,69
3,00	4,10	10,75	10,37	9,99	3,86
3,50	4,18	11,19	10,83	10,47	3,97
4,00	4,21	11,52	11,18	10,84	4,01
5,00	4,07	11,89	11,58	11,28	3,91
6,00	3,67	11,94	11,65	11,38	3,57
7,00	2,93	11,61	11,37	11,15	2,88
8,00	1,39	10,92	10,74	10,58	1,43

Lista produktów

OPIS	Nr katalogowy
EX-protect.emerg.luminaire design EX zone2/22 LED 1h 230V AC without pictogram, wall or ceiling surface mounting, IP66, type: MULTIBASET-N-LED-1300-4K, 320lm	NLEXU011SC
Dodatkowe akcesoria	
Adhesive pictogram, arrow left, viewing distance: 20m Viewing distance: 20m	NLLTPLI
Adhesive pictogram, arrow right, viewing distance: 20m Viewing distance: 20m	NLLTPRE
Adhesive pictogram, arrow up, viewing distance: 20m Viewing distance: 20m	NLLTPOB
Adhesive pictogram, arrow down, viewing distance: 20m Viewing distance: 20m	NLLTPUN
Accu NiCd 3.6V 1.6Ah for self-contained luminaire NLEXU011SC	NLAKKU3616