

Dane techniczne dla produktu: NLKSCS509C

Emergency lum.KS 4x0,5W LED CC24 24V, universal mount., black

with supervision - centrally switchable, with 4x0,5W High Power LED, with transparent cover for additional light of the rescue path, viewing distance: 22m, 220lm



Dane techniczne

Długość (mm)	250,00
Szerokość (mm)	34,00
Wysokość (mm)	174,00
Waga (kg)	0,62
Rodzaj oprawy oświetleniowej	kombinowana awaryjna i ewakuacyjna kierunkowa ewakuacyjna awaryjna
EB-ZB	Zasilacze centralne do opraw
Funkcja	24V Core24 z nadzorem - przełączane centralnie
Wersja	oprawy plastikowe oprawy awaryjne dwustronne
Design / Seria	KS
Bezhalogenowy	obudowa wykonana z tworzywa sztucznego bezhalogenowego

Dane techniczne - kontynuacja


Kolor	RAL 9005 (czarny)
Widoczność (mb)	22
Źródło światła	LED (2W)
Strumień świetlny	220
Zakres napięcia (V)	24V AC
Power maintained mode (W)	2,10
Power non-maintained mode (W)	0,40
Power max. (W)	2,10
Stopień szczelności	IP54
Odporność na uderzenia	≥ IK03
Montaż	naścienny wpuszczany (opcjonalnie) uniwersalny sufitowy natynkowy
Min. temperatura otoczenia (°C)	-5
Maks. temperatura otoczenia (°C)	40
AA Class E 8101	AA4
Producent	Schrack

Abmessungen (mm)

NLKS...



NLKME



Bohrabstände (mm)



Abstandstabelle - Min. Beleuchtungsstärke auf der Mittellinie +/- 0,5m: 1lx - Wartungsfaktor 0,80

					
2,00	3,07	7,54	7,42	6,91	2,76
2,50	2,95	8,36	8,09	7,52	3,13
3,00	1,28	7,33	7,06	8,16	3,24
3,50	1,24	6,66	6,47	8,85	3
4,00	1,27	3,67	6,42	9,15	2,91
5,00	1,15	3,52	5,79	8,41	2,15

Lista produktów

OPIS	Nr katalogowy
Emergency lum.KS 4x0,5W LED CC24 24V,universal mount., black with supervision - centrally switchable, with 4x0,5W High Power LED, with transparent cover for additional light of the rescue path, NLKSCS509C viewing distance: 22m, 220lm	
Dodatkowe akcesoria	
Recessed frame black for CPS luminaires Design KM,KMB,KS Required ceiling cut out: 275 x 54 mm	NLKMES
Piktogram podłączany lewy górny do AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLO
Piktogram podłączany lewy dolny do AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLU
Piktogram podłączany prawy górny do AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRO
Piktogram podłączany prawy dolny do AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRU
Pictograph set "fire protection" VD: 22 m.. (2x4 pcs.) pictographs according to ISO 7010 included: fire extinguisher, fire hose reel, fire alarm call point, collection of firefighting equipment, suitable for design KS, AM, KB	NLKS4FIRE
Pictograph set "first aid" vd: 22m (2x4 pcs.) pictographs according to ISO 7010 included: first aid, Hazard duty point, Automated heart defibrillator, emergency window with escape ladder, suitable for design KS, AM, KB	NLKS4HELP
Wall bracket white for luminaires Design KM/KS	NLAWKSU
Design pair of pendants 500 mm white, wired Suitable for design KS, KM, KMB in self contained version with LiFePO4 battery	NL2DWKMKS
Zawiesie dla opraw KD,KS,LI,M,	NLBALL1
Zawiesie łańcuchowe LI-DESIGN	NLDSA000
Cord suspension 2000mm, 1 pair	NLCORD2
Cord suspension 4000mm, 1 pair	NLCORD4