

Dane techniczne dla produktu: NLKWD009--


suitable for ceiling mounting with pictograms on one or two sides as well as for wall mounting with pictogram on one side, viewing distance: 16m



Dane techniczne

Długość (mm)	360,00
Szerokość (mm)	92,00
Wysokość (mm)	125,00
Waga (kg)	0,70
Rodzaj oprawy oświetleniowej	Oprawa kierunkowa ewakuacyjna
EB-ZB	Zasilacze centralne do opraw
Funkcja	podstawowa
Wersja	oprawy plastikowe
Design / Seria	KW
Bezhalogenowy	Housing made of halogen-free plastic
Kolor	Biały
Widoczność (mb)	16
Źródło światła	HP-LED (3W)
Strumień świetlny	300
Zakres napięcia (V)	230V AC 50Hz ±20%; 230V DC ±20%
Stopień szczelności	IP54
Montaż	Sufitowy natynkowy
AA Class E 8101	AA4
Producent	Schrack

Dimensions (mm)



Distance table - min. illumination at the middle line: 1 lx - maintenance factor 0,80

Montagehöhe [m]					
2,00	2,65	7,29	6,52	5,68	2,07
2,50	2,68	7,58	6,78	5,94	2,02
3,00	2,52	7,69	6,87	6,03	1,87
3,50	2,19	7,63	6,79	5,94	1,56
4,00	1,54	7,39	6,53	5,68	0,92

Lista produktów

OPIS	Nr katalogowy
suitable for ceiling mounting with pictograms on one or two sides as well as for wall mounting with pictogram on one side, viewing distance: 16m	NLKWD009
Dodatkowe akcesoria	
Crystal-clear wall cover for KW	NLKWC
Ball protection gascet for KW	NLBKW
Zestaw piktogramów dla opraw KW	NLKW0103
High Cover for ceiling mounting of emerg. lamp KW, opaque	NLKWH
Zawiesie 500 mm, kolor biały, okablowane	NL2PW
Wall bracket white suitable for: KB, KX, KW, KCD, KE, GX, RX	NLAWX001