

Dane techniczne dla produktu: NLMD0100--

Central Power Supply Midicontrol charger:2,5A / max 32 circ.

without el. circuit module NLDCM42MID, without batteries, with battery compartment upto 55 Ah, H1950 x W600 x D450mm



Dane techniczne

Długość (mm)	450,00
Szerokość (mm)	600,00
Wysokość (mm)	1.950,00
Waga (kg)	105,00

Lista produktów

OPIS	Nr katalogowy
Central Power Supply Midicontrol charger:2,5A / max 32 circ. without el. circuit module NLDCM42MID, without batteries, with battery compartment upto 55 Ah, H1950 x W600 x D450mm	NLMD0100
Niezbędne akcesoria	
Moduł obwodu elektrycznego DCM dla 2 obwodów 19" 2x1A, DS/BS Do centralnych, indywidualnie przełączanych opraw awaryjnych NL...EL, NL...E, maks. obciążenie 2 x 300VA - zabezpieczenie bezpiecznikowe 4x F5A, 6,3x32mm. Nadaje się do systemów baterii grupowych i centralnych Micro-, Mini-, Midi-, Maxi- lub MultiControl.	NLDCM12E
Moduł obwodu elektrycznego DCM dla 2 obwodów 19" 2x3A, DS/BS Maks. obciążenie 2 x 650VA - Zabezpieczenie bezpiecznikowe 4x F5A, 6,3x32mm. Nadaje się do systemów baterii grupowych i NLDCM32 centralnych Micro-, Mini-, Midi-, Maxi- lub MultiControl.	

Lista produktów

OPIS	Nr katalogowy
Niezbędne akcesoria	
Moduł obwodu elektrycznego DCM dla 2 obwodów 19" 2x4A, DS/BS	
Maks. obciążenie 2 x 860VA - Zabezpieczenie bezpiecznikowe 4x F6.3A, 6.3x32mm. Nadaje się do systemów baterii grupowych i centralnych Mini-, Midi-, Maxi- lub MultiControl.	NLDCM42
El. circuit unit DCM 19" 2x4A maint./non-m. for Midicontrol	
Max. load 2 x 860VA – fuse 4x F6,3A, 6,3x32mm. Built in into MidiControl at the factory	NLDCM42MID
Battery set 216V 18 pcs. longlife OGIV 12V/17Ah (C20)	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 1935W/1h 736W/3h 343W/8h, total weight: 99kg, ventilation requirements according to EN 62485-2: Q=0,79m³/h, A=22cm²	NLBAS017
Battery set 216V 18 pcs. longlife OGIV 12V/26Ah (C20)	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2678W/1h 1227W/3h 531W/8h, total weight: 166kg, ventilation requirements according to EN 62485-2: Q=1,2m³/h, A=33,5cm²	NLBAS026
Battery set 216V 18 pcs. longlife OGIV 12V/30Ah (C20)	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2575W/1h 1250W/3h 566W/8h, total weight: 164kg, ventilation requirements according to EN 62485-2: Q=1,34m³/h, A=37,4cm²	NLBAS028
Battery set 216V 18 pcs. longlife OGIV 12V/34Ah (C20)	
Type RPower, incl. cable connectors (NLBAV3375G), battery set suitable for 3421W/1h 1411W/3h 635W/8h, total weight: 198kg, ventilation requirements according to EN 62485-2: Q=1,57m³/h, A=44,1cm²	NLBAS033
Battery set 216V 18 pcs. longlife OGIV 12V/42Ah (C20)	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4061W/1h 1630W/3h 719W/8h, total weight: 248kg, ventilation requirements according to EN 62485-2: Q=1,88m³/h, A=52,6cm²	NLBAS040
Battery set 216V 18 pcs. longlife OGIV 12V/47Ah (C20)	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4579W/1h 1884W/3h 862W/8h, total weight: 263kg, ventilation requirements according to EN 62485-2: Q=2,15m³/h, A=60,1cm²	NLBAS045
Battery set 216V 18 pcs. longlife OGIV 12V/61Ah (C20)	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 6324W/1h 2598W/3h 1194W/8h, total weight: 310kg, ventilation requirements according to EN 62485-2: Q=2,83m³/h, A=79,2cm²	NLBAS055
Dodatkowe akcesoria	
Plexiglas cover with lock for CPS Midicontrol	NLPLXMD
3-phase line monitor with bus communication for Multicontrol	NLMCLM
PC230 3-fazowy monitor faz	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Panel kontrolny z wyświetlaczem LCD i poł. z magistralą	
Do opraw awaryjnych	NLMCT15
Indicator panel with LCD display, key switch and bus comm.	
With key switch	NLMCT15S