

Dane techniczne dla produktu: NLMN102A05

Low Power Supply MiniControl 2 circ. total max. 40 lamps

Max. load: 500W 1h / 200W 3h, optionally extendable to max. 12 electrical circuits 240
luminaires



Dane techniczne

Długość (mm)	230,00
Szerokość (mm)	500,00
Wysokość (mm)	1.100,00
Waga (kg)	140,01

Lista produktów

OPIS	Nr katalogowy
Low Power Supply MiniControl 2 circ. total max. 40 lamps Max. load: 500W 1h / 200W 3h, optionally extenable to max. 12 electrical circuits 240 luminaires	NLMN102A05
Dodatkowe akcesoria	
E30 fire protection panel for LPS MiniControl MN with fan Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPLXMIN
3-phase line monitor with bus communication for Multicontrol	NLMCLM
PC230 3-fazowy monitor faz	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Panel kontrolny z wyświetlaczem LCD i poł. z magistralą Do opraw awaryjnych	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S