

Dane techniczne dla produktu: NLMN110A--

Low Power Supply MiniControl 10 circ. total max. 200 lumin.

10 electrical circuits, max. 200 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm



Dane techniczne

Długość (mm)	230,00
Szerokość (mm)	500,00
Wysokość (mm)	1.100,00
Waga (kg)	140,01

Lista produktów

OPIS	Nr katalogowy
Low Power Supply MiniControl 10 circ. total max. 200 lumin.	
10 electrical circuits, max. 200 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm	NLMN110A
Dodatkowe akcesoria	
E30 fire protection panel for LPS MiniControl MN with fan	
Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPXMIN
3-phase line monitor with bus communication for Multicontrol	NLMCLM
PC230 3-fazowy monitor faz	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Panel kontrolny z wyświetlaczem LCD i poł. z magistralą	
Do oprav awaryjnych	NLMCT15
Indicator panel with LCD display, key switch and bus comm.	
With key switch	NLMCT15S