

Dane techniczne dla produktu: SR3PDIPP04

PDU PRO Metered+, 36xCombo (C13,C15,C19,C21), 400V, 16A, RCM

Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+ inkl. RCM
- Metering per socket
- Residual Current Monitoring per phase, Typ B
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Dane techniczne

Długość (mm)	1.696,50
Szerokość (mm)	56,00
Wysokość (mm)	71,00
EAN	4057298230332
Sugerowana cena detaliczna	24.790,00
Min. temperatura otoczenia (°C)	0
Maks. temperatura otoczenia (°C)	50
Napięcie znamionowe	400V
Stopień szczelności	IP20
Typ produktu	z pomiarem+
Liczba gniazd	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Prąd znamionowy (A)	16
Phases per feed	3
Typ podłączenia	CEE 16 A czerwony
Protokół	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montaż	Wspornik montażowy (kształt litery L)

OPIS	Nr katalogowy
PDU PRO Metered+, 36xCombo (C13,C15,C19,C21), 400V, 16A, RCM	SR3PDIPP04
Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws	