

Dane techniczne dla produktu: SR3PDIPP05

PDU PRO Metered+, 24xgniazdo kombi (C13, C15, C19, C21), 230V, 32A

Metering per outlet, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 32 A / 230 V | 7,2 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A blue
- Output: 24x Combo C13/C15/C19/C21
- 2x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

Dane techniczne

Długość (mm)	1.318,20
Szerokość (mm)	56,00
Wysokość (mm)	71,00
EAN	4057298230363
Sugerowana cena detaliczna	18.050,00
Min. temperatura otoczenia (°C)	0
Maks. temperatura otoczenia (°C)	50
Napięcie znamionowe	230V
Stopień szczelności	IP20
Typ produktu	z pomiarem+
Liczba gniazd	24
Outlet type	24 x Combo Socket (C13/C15/C19/C21)
Prąd znamionowy (A)	32
Phases per feed	1
Typ podłączenia	CEE 32 A niebieski
Protokół	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montaż	Wspornik montażowy (kształt litery L)

OPIS	Nr katalogowy
PDU PRO Metered+, 24xgniazdo kombi (C13, C15, C19, C21), 230V, 32A Metering per outlet, incl. mounting bracket with screws	SR3PDIPP05