

Dane techniczne dla produktu: SR3PDIPP07

PDU PRO Metered+, 36xgniazdo kombi (C13, C15, C19, C21), 400V, 32A

Metering per outlet, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x Combo C13/C15/C19/C21
- 6x hydraulisch-magnetische LS-Schalter 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

Dane techniczne

Długość (mm)	1.950,30
Szerokość (mm)	56,00
Wysokość (mm)	71,00
EAN	4057298230417
Sugerowana cena detaliczna	25.630,00
Min. temperatura otoczenia (°C)	0
Maks. temperatura otoczenia (°C)	50
Napięcie znamionowe	400V
Stopień szczelności	IP20
Typ produktu	z pomiarem+
Liczba gniazd	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Prąd znamionowy (A)	32
Phases per feed	3
Typ podłączenia	CEE 32 A czerwony
Protokół	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montaż	Wspornik montażowy (kształt litery L)

OPIS	Nr katalogowy
PDU PRO Metered+, 36xgniazdo kombi (C13, C15, C19, C21), 400V, 32A Metering per outlet, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!	SR3PDIPP07