

Dane techniczne dla produktu: WSAIE4040P

Wkład modułowy WSA 3-rzędowy (3 x 17M) do H=400 W=400mm

Pasuje do WSA4040210



SCHRACK-Info


- For installation of modular devices on DIN-rails
- The distance between the DIN-rails (centre-centre) is:
 - 120mm at WSAIE6040P, WSAIE7050P, WSAIE8060P, WSAIE1080P and WSAIE1280P
 - 130mm at WSAIE5040P, WSAIE1060P and WSAIE1260P
 - 140mm at WSAIE4030P and WSAIE4040P
- The usable depth between the front cover of the WSAIE modular chassis and the WSA enclosure door is 32.5mm
- Material thickness: 1.2mm
- Degree of protection: IP3XD according to IEC 60529
- Color: RAL 7035 (Light grey)
- Supply includes:
 - 1 Piece of front door with 45mm cutouts
 - 2 Pieces of vertical profiles
 - 2 Pieces of closures (top/bottom)
 - DIN-rails
 - Mounting material

Dane techniczne

Dane techniczne - kontynuacja

Szerokość (mm)	400,00
Wysokość (mm)	400,00
Głębokość (mm)	61,00
Waga (kg)	3,30
Kolor	RAL 7035 (jasnoszary)

Rysunek wymiarowy: Wkład modułowy WSA 3-rzędowy (3 x 17M) do H=400 W=400mm



Wkład modułowy WSA 3-rzędowy (3 x 17M) do H=400 W=400mm

WSAIE4040P

Pasuje do WSA4040210